



SPECIFICATIONS

MATERIAL:

- 1. Housing : NYLON46 UL94V0
- 2. Color : Black
- 3. Contacts : 0.35mm Thickness Alloy Selective Gold Plating

ELECTRICAL:

- 1. Current Rating : 1.5 AMP MAX
- 2. Voltage Rating : 150 VAC MAX
- 3. Contact Resistance : 30 milliohms MAX, initial
- 4. Insulation Resistance : 500 Megohms MIN
- 5. Dielectric Withstanding Voltage : 1000 VAC, 1min

UL. CUL NO.: E166003

Ordering Information

370-1XX2-10XS1

- W/O Split Pegs
- 2 - Grounding Tab
- 4 - Grounding Pin

No. of Contacts

2,4,6,8,1(10C)

Gold Plating

- 2 - 6u"
- 3 - 15u"
- 4 - 30u"
- 5 - 50u"

PCB LAYOUT

.X ±0.3	UNITS	mm	DWG NO.:	TITLE: Side Entry Very L/P Modular Jack W/O Split Pegs(SMT)
	.XX ±0.20		SCALE	
		Free	CHKD:	PART NO.:
TOLERANCE			DR: S. K. Liu	370-1XX2-10XS1
			SHEET: 1/1	皇杰興業有限公司 FINE JACK INDUSTRIAL CO., LTD
			REV: A	
			DATE: 07/28/03	