



PCB LAYOUT

**SPECIFICATIONS**

**MATERIAL:**

1. Housing : NYLON46 UL94V0
2. Color : Black
3. Contacts : 0.35mm Thickness Alloy Selective Gold Plating
4. Shield : 0.25mm Thickness Copper Alloy With Nickel Plated

**ELECTRICAL:**

1. Current Rating : 1.5 AMP MAX
2. Voltage Rating : 150 VAC MAX
3. Contact Resistance : 30 milliohms MAX, initial
4. Insulation Resistance : 500 Megohms MIN
5. Dielectric Withstanding Voltage : 1000 VAC, 1min

UL. CUL NO.: E166003

**Ordering Information**

370S-1XX2-1XXS1

No. of Contacts  
2,4,6,8,1(10C)

Gold Plating  
2 - 6u"  
3 - 15u"  
4 - 30u"  
5 - 50u"

W/O Split Pegs  
1 - Grounding Tab  
2 - Grounding Pin

Panel Grounding  
1 - W/O P.G. Tab  
2 - Top P.G. Tab  
3 - Top & Side P.G. Tab

.X ±0.3	UNITS	DWG NO.:	TITLE: Side Entry Very L/P Shielded Modular Jack W/O Split Pegs(SMT)
	mm		
.XX ±0.20	SCALE	APPD: C. T. Tsai	PART NO.:
	Free	CHKD:	
TOLERANCE		DR: S. K. Liu	370S-1XX2-1XXS1
	SHEET:	1/1	<b>皇杰興業有限公司</b> FINE JACK INDUSTRIAL CO., LTD
	REV:	A	
	DATE:	07/28/03	