


PCB LAYOUT/TOP VIEW



SPECIFICATIONS

MATERIAL:

- 1. Housing : PBT Polyester UL94V0
- 2. Color : Black
- 3. Contacts : 0.45mm Diameter Phos-Bronze Plated With Hard Gold

ELECTRICAL:

- 1. Current Rating : 1.5 AMP
- 2. Voltage Rating : 150 VAC
- 3. Contact Resistance : 30 Milliohms MAX
- 4. Insulation Resistance : 500 Milliohms MIN
- 5. Dielectric Withstanding Voltage : 1000 VAC, 1min

UL. CUL NO.: E166003

Ordering Information

623KL-6XX1-10001

No. of Contacts 2,4,6	┌	Gold Plating
		1 - 3u"
		2 - 6u"
		3 - 15u"
		4 - 30u"
		5 - 50u"

.X ±0.3	UNITS	DWG NO.:	TITLE:
	mm		
.XX ±0.20	SCALE	APPD: C. T. Tsai	6P Side Entry Modular Jack
	Free	CHKD:	PART NO.:
TOLERANCE		DR: S. K. Liu	623KL-6XX1-10001
	SHEET: 1/1	皇杰興業有限公司 FINE JACK INDUSTRIAL CO., LTD	
	REV: A		
	DATE: 07/28/03		