



PCB LAYOUT

**SPECIFICATIONS**

**MATERIAL:**

1. Housing : PPS. Polyester UL94V0
2. Color : Black
3. Contacts : Selective Gold Plating
4. Shield : 0.20mm Thickness C2680 Alloy With Au and Nickel Plated

**ELECTRICAL:**

1. Current Rating : 1.5 AMP MAX
2. Voltage Rating : 150 VAC MAX
3. Contact Resistance : 30 milliohms MAX, initial
4. Insulation Resistance : 500 Megohms MIN
5. Dielectric Withstanding Voltage : 1000 VAC, 1min

UL. CUL NO.: E166003

**Ordering Information**

623KRS-6XX2-11001

No. of Contacts	623KRS-6XX2-11001	Gold Plating
	2	- 6u"
	3	- 15u"
	4	- 30u"
	5	- 50u"

.X ±0.3	UNITS	DWG NO.:	TITLE:
	mm	APPD: C. T. Tsai	RJ11 6P Shielded Modular Jack (SMT)
.XX ±0.20	SCALE	CHKD:	PART NO.:
	Free	DR: S. K. Liu	623KRS-6XX2-11001
TOLERANCE		SHEET: 1/1	<b>皇杰興業有限公司</b> FINE JACK INDUSTRIAL CO., LTD
		REV: A	
		DATE: 07/28/03	