



PCB LAYOUT

SPECIFICATIONS

MATERIAL:

1. Housing : PPS. Polyester UL94V0
2. Color : Black
3. Contacts : Selective Gold Plating
4. Shield : 0.20mm Thickness C2680 Alloy With Au and Nickel Plated

ELECTRICAL:

1. Current Rating : 1.5 AMP MAX
2. Voltage Rating : 150 VAC MAX
3. Contact Resistance : 30 milliohms MAX, initial
4. Insulation Resistance : 500 Megohms MIN
5. Dielectric Withstanding Voltage : 1000 VAC, 1min

UL. CUL NO.: E166003

Ordering Information

623KRS-8XX2-11001

No. of Contacts 2,4,6,8	Gold Plating
	2 - 6u"
	3 - 15u"
	4 - 30u"
	5 - 50u"

.X ±0.3	UNITS	DWG NO.:	TITLE:
	mm	APPD: C. T. Tsai	RJ45 8P Shielded Modular Jack (SMT)
.XX ±0.20	SCALE	CHKD:	PART NO.:
	Free	DR: S. K. Liu	623KRS-8XX2-11001
TOLERANCE		SHEET: 1/1	皇杰興業有限公司 FINE JACK INDUSTRIAL CO., LTD
		REV: A	
		DATE: 07/28/03	