



PCB LAYOUT/TOP VIEW

SPECIFICATIONS

MATERIAL:

1. Housing : PBT Polyester UL94V0
2. Color : Black
3. Contacts : 0.35mm Thickness Alloy Selective Gold Plating
4. Shield : 0.25mm Thickness Copper Alloy With Nickel Plated

ELECTRICAL:

1. Current Rating : 1.5 AMP MAX
2. Voltage Rating : 150 VAC MAX
3. Contact Resistance : 30 milliohms MAX, initial
4. Insulation Resistance : 500 Megohms MIN
5. Dielectric Withstanding Voltage : 1000 VAC, 1min

UL. CUL NO.: E166003

Ordering Information

623KV(HS)-XXX2-11411

No. of Positions 6,8	Gold Plating	2 - 6u"
		3 - 15u"
No. of Contacts 2,4,6,8	Gold Plating	4 - 30u"
		5 - 50u"

No. of Positions	Dimensions m/m				
	A	B	C	D	E
6	13.83	10.16	6.35	15.74	13.58
8	15.86	11.43	8.89	17.40	15.75

.X ±0,3	UNITS	DWG NO.:	TITLE:
	mm		
.XX ±0,20	SCALE	CHKD:	PART NO.:
		DR: S. K. Liu	623KV(HS)-XXX2-11411
TOLERANCE		SHEET: 1/1	皇杰興業有限公司 FINE JACK INDUSTRIAL CO., LTD
		REV: A	
		DATE: 07/28/03	