



PCB LAYOUT/TOP VIEW

SPECIFICATIONS

MATERIAL:

1. Housing : PBT Polyester UL94V0
2. Color : Black
3. Contacts : 0.35mm Thickness Alloy Selective Gold Plating

ELECTRICAL:

1. Current Rating : 1.5 AMP MAX
2. Voltage Rating : 150 VAC MAX
3. Contact Resistance : 30 milliohms MAX, initial
4. Insulation Resistance : 500 Megohms MIN
5. Dielectric Withstanding Voltage : 1000 VAC, 1min

UL. CUL NO.: E166003

Ordering Information

623KV-XXX2-100X1

No. of Positions: 6,8,1(10P)
 No. of Contacts: 2,4,6,8,1(10C)
 Gold Plating: 2 - 6u", 3 - 15u", 4 - 30u", 5 - 50u"

Panel Stop:
 0 - W/O Panel Stop
 1 - W/Panel Stop

No. of Positions	Dimensions m/m			
	A	B	C	D
6	13.20	10.16	6.35	15.60
8	15.10	11.43	8.89	17.40

.X ±0.3	UNITS	DWG NO.:	TITLE:
	mm		
.XX ±0.20	SCALE	APPD: C. T. Tsai	PART NO.:
		CHKD:	
TOLERANCE		DR: S. K. Liu	皇杰興業有限公司 FINE JACK INDUSTRIAL CO., LTD
		SHEET: 1/1	
		REV: A	
		DATE: 07/28/03	