



**SPECIFICATIONS**

**MATERIAL:**

- 1. Housing : PBT Polyester UL94V0
- 2. Color : Black
- 3. Contacts : 0.45mm Diameter Phos-Bronze Plated With Hard Gold

**ELECTRICAL:**

- 1. Current Rating : 1.5 AMP MAX
- 2. Voltage Rating : 150 VAC MAX
- 3. Contact Resistance : 30 milliohms MAX, initial
- 4. Insulation Resistance : 500 Megohms MIN
- 5. Dielectric Withstanding Voltage : 1000 VAC, 1min

**Ordering Information**

623MLP-1XX1-X00X1

- Panel Stop
  - 0 - W/O Panel Stop
  - 1 - W/Panel Stop
- No. of Contacts
  - 2,4,6,8,1(10C)
- Gold Plating
  - 1 - 3u"
  - 2 - 6u"
  - 3 - 15u"
  - 4 - 30u"
  - 5 - 50u"
- No. of Ports
  - 1 - 1 Port
  - 2 - 2 Ports

Ports	Dimensions m/m		
	A	B	C
1	17.00	15.00	15.00
2	32.00	30.00	30.00

PCB LAYOUT/TOP VIEW

.X ±0.3	UNITS	DWG NO.:	TITLE:
	mm		
.XX ±0.20	SCALE	CHKD:	PART NO.:
	Free		
TOLERANCE		SHEET: 1/1	皇杰興業有限公司 FINE JACK INDUSTRIAL CO., LTD
		REV: A	
		DATE: 11/20/03	